



**T5000-24 plus**  
now certified for handling  
UHP and run-flat tyres





## T5000-24 plus

The T5000-24 plus was certified; it is now released for handling all UHP and run-flat tyres.

- The T5000-24 with pneumatic mounting tool MH 320 has undergone a redesign and is now also certified for the gentle and user-friendly mounting and demounting of UHP and runflat tyres in line with OEM specifications.
- The innovative triangular bead pusher prevents the tyre from being damaged and retains it in optimum position in the drop centre of the rim.
- The bead breaker disc demounts the tyre in an especially gentle way, pushing it down in the drop centre of the rim.
- The specially shaped tyre lever levers the bead over the nose of the mounting head without risking any damage.
- Max. outer clamping capability is 24".
- The tyre changer is equipped with a double-acting bead breaking cylinder and a large bead breaker blade to make sure tyres and rims remain undamaged.
- Alloy rims are handled especially gently as mounting head and clamping jaws are provided with plastic protections. In addition the single-part mounting head can be adjusted vertically and laterally in spaced-apart position relative to the rim.
- User-friendliness is ensured thanks to the automatically tilt-back post and the four ergonomic pedals.
- The self-centring four-jaw chuck controlled by two clamping cylinders provides for quick and accurate clamping, exact locking of the post expedites operation even more.

### TECHNICAL DATA AND STANDARD EQUIPMENT

Technical data		
Clamping range: inside	inch	14 – 24
Clamping range: outside	inch	12 – 24
Rim width	inch	3 – 14
Max. tyre width	inch	15
Max. wheel diameter	mm	1000
Bead breaking range	mm	40 – 440
Max. bead breaking range	mm	440
Compressed air supply	bar	8 – 12
Machine dimensions (W x D x H)	mm	1180 x 1310 x 1610
Weight	kg	345
Power supply		3 / PE AC 400 – 415 V / 50 / 60 Hz
Chuck speed	rpm	7 / 13

Standard equipment
Plastic rim protection
Plastic tyre protection
Plastic protection for bead breaker blade
Spacers for bead breaker blade
Tyre lever Plus
Magic bead pusher MBP
Triangular bead pusher
Rod with tapered roll
Plastic bead breaker disc
Roller board

## Snap-on Equipment

**France:** Snap-on Equipment France  
 ZA du Vert Galant · 15, rue de la Guivernone BP97175, ST Ouen L'Aumone · 95056 Cergy Pontoise Cedex  
 Phone: +33 (0) 134/48 58-78 · Fax: +33 (0) 134/48 58-70 · www.snapon-equipment.fr

**Germany:** Snap-on Equipment GmbH – Undercar · Werner-von-Siemens-Str. 2 · 64319 Pfungstadt  
 Phone: +49 (0) 6157/12-0 · Fax: +49 (0) 6157/12-286 · www.snapon-equipment.de

**Italy:** Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)  
 Phone: +39 0522/733-411 · Fax: +39 0522/733-410

**United Kingdom:** Snap-on Equipment Ltd. · 48 Sutton Park Avenue · Reading RG6 1AZ  
 Phone: +44 (0) 118/929-6811 · Fax: +44 (0) 118/966-4369 · www.johnbean.co.uk

**EMEA-JA:** Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)  
 Phone: +39 0522/733-483 · Fax: +39 0522/733-479 · www.snapon-equipment.eu